

CEILING MOUNTED CASSETTE 4-WAY FLOW

- > 4-Way Air Flow
- > Optimal comfort and convenience assured by air discharge modes
- > Compact Body & Quiet Operation

		2 PK	2.5 PK	3 PK	3 PK	4 PK	5 PK
Model	Indoor	FCRN50FXV14	FCRN60FXV14	FCRN71FXV14	FCRN71FXV14	FCRN100FXV14	FCRN125FXV14
	Outdoor	RN50CXV1A4	RN60CXV1A4	RR71CXV1A4	RR71CXY1A4	RR100DXY1A4	RR125DXY1A4
Catu daya		V: 220-240V, 1 \emptyset , 50Hz / 220-230V, 1 \emptyset , 60Hz			Y: 380-415V, 3 \emptyset , 50Hz		
Kapasitas	Btu/h	18,500	23,000	28.000	28.000	36.000	42.000
	kW	5.42	6.74	8.21	8.21	10.55	12.13
Daya Listrik	KW	1.76	2.05	2.93	2.90	3.66	4.11
COP	W/W	3.08	3.29	2.80	2.83	2.88	3.00
Indoor	Dimensi (HxWxD)	mm 246x840x840			mm 246x840x840		
	Berat Mesin	kg 22			kg 22		kg 25
Outdoor	Dimensi (HxWxD)	mm 651x855x328		mm 753x855x328		mm 852x1,030x428	
	Berat Mesin	kg 43	kg 47	kg 57	kg 56	kg 71	kg 95
Ukuran Pipa	Cair	inch 1/4		inch 3/8			
	Gas	inch 1/2	inch 5/8	inch 5/8			
Maksimal Pipa	Panjang	m 30		m 45		m 50	
	Tinggi	m 15		m 25		m 30	