

Ceiling Mounted Cassette Round Flow

Easy Installation

Quick and easy to install
 Panel-hook mechanism
 Detachable corner
 Position of connecting pipe and drain hose
 Easy accessible control box
 Drain pump is equipped as standard accessory with 700 mm lift

Easy Maintenance

Easier to maintain
 Simple step to change fan motor
 Self-diagnosis function

		1.5 PK	2 PK	2.5 PK	3 PK	3 PK	3.5 PK
Model	Indoor	FCNQ13MV14	FCNQ18MV14	FCNQ21MV14	FCNQ26MV14	FCNQ26MV14	FCNQ30MV14
	Outdoor	RNQ13MY14	RNQ18MY14	RNQ21MY14	RNQ26MY14	RNQ26MY14	RNQ30MY14
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz				Y: 380-415V, 3Ø, 50Hz	
Kapasitas	Btu/h	13,000	18,000	21,000	26,000	26,000	30,000
	kW	3.8	5.3	6.2	7.6	7.6	8.8
Daya Listrik	KW	1.24	1.89	2.21	2.53	2.53	2.73
COP	W/W	3.07	2.80	2.80	3.00	3.00	3.22
Indoor	Dimensi (HxWxD)	256x840x840			256x840x840		298x840x840
	Berat Mesin	19.5		21	21		24
Outdoor	Dimensi (HxWxD)	550x765x285	595x845x300		735x825x300		990x940x320
	Berat Mesin	36	40	49	56		74
Ukuran Pipa	Cair	1/4			3/8		
	Gas	1/2		5/8	5/8		
Maksimal Pipa	Panjang	30			30		50
	Tinggi	10	15		20		30

		4 PK	5 PK	6 PK
Model	Indoor	FCNQ36MV14	FCNQ42MV14	FCNQ48MV14
	Outdoor	RNQ36MY14	RNQ42MY14	RNQ48MY14
Catu daya		Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h	36,000	42,600	48,000
	kW	10.6	12.5	14.1
Daya Listrik	KW	3.31	4.15	5.04
COP	W/W	3.20	3.01	2.80
Indoor	Dimensi (HxWxD)	298x840x840		
	Berat Mesin	24		
Outdoor	Dimensi (HxWxD)	1,345x900x320		
	Berat Mesin	103	107	111
Ukuran Pipa	Cair	3/8		
	Gas	5/8		
Maksimal Pipa	Panjang	50		
	Tinggi	30		